

ORDERING INFORMATION:


PART NUMBER: FP-1 - T - W - L
EXAMPLE: FP-1 - 1/4 - 4 - 12

FP-1 FLAT PAD
 1/4 THICKNESS
 4 WIDTH
 12 LENGTH

NOTES:

1. RedLineIPS Composite Flat Pads are made from vinyl ester resin material, as manufactured by Cogbill Construction.
2. RedLineIPS Composite Flat Pads shall be installed as per the RedLineIPS installation procedures.
3. Produced in either 1/8" or 1/4" thicknesses. To be specified by customer.
4. Operating Temperature Range: -67°F (-55°C) to +400°F (204°C).
5. Epoxy fillet to be one continuous bead all around the wear pad for sealing it to the support steel.
6. Compressive load capacity rating of 113,000 lbs.
7. Length and width is sized to fit support steel, minus 1/2" clearance in order to seal. To be specified by customer.

REV	DESCRIPTION	BY	CHK.	DATE	PIPING STANDARD DETAILS	
					RedLineIPS NON-METALLIC FLAT PADS	
0	ISSUED FOR CONSTRUCTION	GT	HA	12/18/2018	DRAWING NUMBER:	FP-1
A	ISSUED FOR APPROVAL	GT	HA	12/04/2018		



2325 S MAIN ST. VIDOR, TX 77662
 409-768-1419
 www.RedLineIPS.com
 Info@RedLineIPS.com

DRAWN BY: GT 12/04/18	CHK'D BY: HA 12/04/18	REV: 0
APPD BY: WC 12/04/18	SCALE: NTS	SHEET: 1 OF 1