

ORDERING INFORMATION:

PART NUMBER: WP-1 - NPS - T - A - L

EXAMPLE: WP-1 - 8 - 1/4 - 60 - 12


- WP-1 WEAR PAD
- 8 NOMINAL PIPE SIZE
- 1/4 THICKNESS
- 60 PIPE COVERAGE ANGLE
- 12 LENGTH

PIPE SIZE (NPS)	PAD THK. "T" (NOTE 3)	STANDARD ANGLE "A" (NOTE 3)	STANDARD LENGTH "L" (NOTE 3)
INCHES	IN.		
3/4" - 4"	1/4"	90°	12"
6" - 10"	1/4"	60°	12"
12" - 20"	1/4"	30°	12"
24" - 48"	3/8"	30°	18"

OTHER SIZES AVAILABLE, CONTACT COGBILL FOR MORE INFORMATION

NOTES:

1. RedLineIPS Wear Pads are made from vinyl ester resin material, as manufactured by Cogbill Construction.
2. RedLineIPS Wear Pads shall be installed as per the RedLineIPS installation procedures.
3. Various thicknesses, angles of coverage, and lengths are based on the specific design parameters of the piping system and are available upon request.
4. Operating Temperature Range: -67°F (-55°C) to +400°F (204°C).
5. Epoxy fillet to be one continuous bead all around the wear pad for sealing it to the pipe.
6. 50,000 lbs maximum vertical load.
7. RedLineIPS wear pads are suitable for use on all metallic or non-metallic pipes.

REV	DESCRIPTION	BY	CHK.	DATE	PIPING STANDARD DETAILS				
					 <p>2325 S MAIN ST. VIDOR, TX 77662 409-768-1419 www.RedLineIPS.com Info@RedLineIPS.com</p>				
0	ISSUED FOR CONSTRUCTION	GT	HA	12/18/2018	DRAWING NUMBER:	WP-1	DRAWN BY: GT 12/04/18	CHK'D BY: HA 12/04/18	REV: 0
A	ISSUED FOR APPROVAL	GT	HA	12/04/2018			APPD BY: WC 12/04/18	SCALE: NTS	SHEET: 1 OF 1